

# DHI-NVR2104HS-P-4KS3

4CH Compact 1U 4PoE 1HDD Lite Network Video Recorder



- Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.
- Max. decoding capability: 6 × 1080p@30 fps.
- Max. 80/80/60 Mbps incoming/recording/outgoing bandwidth.
- Supports IP cameras with a resolution up to 12 MP.
- AI by Recorder supports 4-channel SMD Plus.
- AI by Camera supports perimeter protection and SMD Plus.
- Supports one-click arming and disarming.



## Series Overview

The NVR2000-4KS3 model of the Lite Series NVR is favored for its outstanding performance. It supports 4K resolution for scenes that require highly detailed images, and can serve as the edge, central, or backup storage with an intuitive shortcut menu for remote management and control. This NVR also features Smart Motion Detection (SMD) by recorder, which can distinguish target vehicles and humans from ordinary ones in real-time. This NVR is both cost-effective and easy-to-install, making it ideal for a wide range of applications such as villas, shops and other small and medium-sized scenes.

## Functions

### SMD Plus

With intelligent algorithm, Dahua Smart Motion Detection technology can categorize the targets that trigger motion detection and filter the motion detection alarm triggered by non-concerned targets to realize effective and accurate alarm.

### Perimeter Protection by Camera

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improves alarm accuracy.

## Technical Specification

System	
Main Processor	Industrial-grade processor
Operating System	Embedded Linux
Operating Interface	Web, Local GUI
AI	
AI by Recorder	SMD Plus
AI by Camera	Perimeter protection; SMD Plus
Perimeter Protection	
Perimeter Performance of AI by Camera (Number of Channels)	4 channels
SMD Plus	
SMD Plus by Recorder	4 channels: Secondary filtering for human and motor vehicle, reducing false alarms caused by leaves, rain and lighting condition change
SMD Plus by Camera	4 channels
Audio and Video	
Access Channel	4 channels
Network Bandwidth	80 Mbps incoming, 80 Mbps recording and 60 Mbps outgoing
Resolution	12 MP; 8 MP; 5 MP; 4 MP; 3 MP; 1080p; 720p; D1
Decoding Capability	AI disabled: 1-channel 12 MP@30 fps; 1-channel 8 MP@30 fps; 2-channel 5 MP@30 fps; 3-channel 4 MP@30 fps; 6-channel 1080p@30 fps AI enabled: 1-channel 8 MP@30 fps; 1-channel 5 MP@30 fps; 2-channel 4 MP@30 fps; 4-channel 1080p@30 fps

## NVR2000-4KS3 Series | DHI-NVR2104HS-P-4KS3

Video Output	1 HDMI, 1 VGA HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720
Multi-screen Display	1/4
Third-party Camera Access	ONVIF

### Compression Standard

Video Compression	Smart H.265+; H.265; Smart H.264+; H.264; MJPEG
Audio Compression	G.711a; G.711u; PCM; G.726;

### Network

Network Protocol	HTTP; HTTPS; TCP/IP; IPv4; IPv6; UDP; NTP; DHCP; DNS; SMTP; IP Filter; DDNS; IP Search (Supports IP camera, DVR, NVS, etc.); P2P; Auto Registration
Mobile Phone Access	iOS; Android
Interoperability	ONVIF 22.12(Profile T; Profile S; Profile G); CGI; SDK
Browser	Chrome; IE; Safari; Edge; Firefox

### Recording Playback

Multi-channel Playback	Up to 4 channels
Record Mode	General, motion detection; intelligent; alarm
Backup Method	USB device and network
Playback Mode	Instant playback; general playback; event playback; tag playback; smart playback

### Alarm

General Alarm	Motion detection; camera external alarm; PIR alarm
Anomaly Alarm	Error (no disk, disk error, low space, low quota space; network disconnection; IP conflict; MAC conflict); video loss; video tampering; camera offline
Intelligent Alarm	Perimeter protection; SMD Plus
Alarm Linkage	Recording; snapshot; buzzer; log; preset; email; tour

### Port

Audio Input	1-channel RCA
Audio Output	1-channel RCA
Alarm Input	NA (2 channels are optional)
Alarm Output	NA (1-channel 12 V 1 A output is optional)
HDD Interface	1 SATA port. Each disk can contain up to 20 TB. this limit varies depending on the environment temperature.
USB	2 (1 front USB 2.0 port, 1 rear USB 2.0 port)
HDMI	1
VGA	1
Network Port	1 (10/100 Mbps Ethernet port, RJ-45)
PoE Port	4 ports, 10/100 Mbps, IEEE 802.3 af/at

### General


Power Supply	53 VDC, 1.22 A
Power Consumption	Total output of NVR is <10 W (without HDD) Total output power of PoE is 36 W, the maximum output power of a single port is 25.5 W

Net Weight	0.85 kg (1.87 lb)
Gross Weight	1.85 kg (4.08 lb)
Product Dimensions	260.0 mm × 232.5 mm × 47.6 mm(10.24" × 9.15" × 1.87") (W × D × H)
Packaging Dimensions	374.0 mm × 119.0 mm × 311.0 mm(14.72" × 4.69" × 12.24")(W × D × H)
Operating Temperature	-10 °C to +55 °C (14 °F to +131 °F)
Storage Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Operating Humidity	10%–93% (RH), non-condensing
Installation	Rack or desktop
Certifications	CE-LVD: IEC 62368-1:2014 CE-EMC: EN IEC 61000-3-2:2019, EN 61000-3-3:2013+A1:2019, EN 55032:2015+A11:2020, EN 55035:2017+A11:2020, EN 55024:2010+A1:2015, EN 50130-4:2011+A1:2014


### Ordering Information

Type	Model	Description
NETWORK VIDEO RECORDER	DHI-NVR2104HS-P-4KS3	4CH Compact 1U 4PoE 1HDD Lite Network Video Recorder

### Dimensions (mm[inch])



**Panels**



- |   |                          |   |                         |
|---|--------------------------|---|-------------------------|
| 1 | AUDIO OUT, RCA Connector | 2 | Power Input             |
| 3 | PoE Ports                | 4 | Network Port            |
| 5 | VGA Port                 | 6 | AUDIO IN, RCA Connector |
| 7 | HDMI Port                | 8 | USB Port                |
| 9 | Ground                   |   |                         |