



USER MANUAL

4K 120M HDMI Extender

Enjoy the vivid world


Introduction

The Extender uses single cat5e or cat6(recommended) cables instead of HDMI cable to transmit high definition signal up to 120 meters, The Extender is designed to supply for long distance transmission of high definition signal.



Features :

- * Support 120m long distance transmission :



- * Low power consumption, low temperature and high safety ;


Specifications:

Length of CAT5e/CAT6 cable between Rx and TX	120 meters
HDMI Input	4k/1080p/720p/576p/576i/480p/480i
HDMI Output	4k/1080p/720p/576p/576i/480p/480i
Max bandwidth	340MHz
Max baud rate	3x3.4Gbps
Input video signal	0.5~1.5Volts p-p
Output DDC signal	5Volts p-p (TTL)
Input HDMI cable distance	≤10m AWG26 HDMI standard cable
Output HDMI cable distance	≤10m AWG26 HDMI standard cable
TX Max working current	500mA
RX Max working current	300mA
Operating Temperature range	(0 to +45 ℃)
Operating Humidity range	5 to 90%RH (No Condensation)
Dimension (L x W x H)	64x59x22(mm)
TX Weight	53g
RX Weight	53g

Connecting and Operating:

- 1.Connect one HDMI cable between source device and TX Extender, the max cable distance is 10 meters
- 2.Connect one HDMI cable between display device and RX Extender, the max cable distance is 10 meters
- 3.Connect single cat-5e or cat-6(recommended) cables instead of HDMI cables between TX and RX Extender, the max cable distance is 120 meters
- 4.Connect 5V power supply to the TX and RX.
- 6.EDID button: The button can support the switch of EDID between 1080P and 4K.(4K is the default EDID when the power is on).

Connection diagram:



Application diagrams

HDMI extender over IP is used in audio-visual conference, command and control center, ticketing platform, home theater, multi-media teaching, conference system and so on.



Audio-visual conference




Command and control center



Home theater

Physical interface diagram



Port	Function description
Input	HDMI Input port
DC/5V	5V DC Power input port
CAT5E/6	Cat5e/6 cable connection port
EDID	4K and 1080P switch button (press for 3 seconds)



Port	Function description
Output	HDMI Output port
DC/5V	5V DC Power input port
CAT5E/6	Cat5e/6 cable connection port

The Package includes:

- | | | | |
|----------------|------|--------------------|------|
| 1. TX Extender | 1PCS | 3. Micro USB Cable | 2PCS |
| 2. RX Extender | 1PCS | 4. User Manual | 1PCS |